

## AMENDMENTS TO THE CLAIMS

1. (CURRENTLY AMENDED) A method for processing a video signal, comprising the steps of:

(A) receiving said video signal comprising (i) a first segment having a series of frames, wherein (a) each of said frames of said first segment has having a first region and a second region, and (b) said first region and said second region of said first segment define defining a first signature for each of said frames of said first segment and (ii) a second segment having a series of frames, wherein (a) each of said frames of said second segment has having a first region and a second region, and (b) said first region and said second region of said second segment define defining a second signature for each of said frames of said second segment;

(B) modifying each of said frames of said first segment from said first signature to a third signature, wherein said first segment comprises a non-commercial program; and

(C) modifying each of said frames of said second segment from said second signature to a fourth signature.

2. (ORIGINAL) The method according to claim 1, wherein said second signature is equal to said fourth signature.

3. (PREVIOUSLY PRESENTED) The method of claim 1, wherein (i) said second segment comprises a commercial program and (ii) said signature modification is performed to suppress the detection of commercials in said video signal.

4. (ORIGINAL) The method according to claim 1, wherein transitions between said first and second segments are not detectable.

5. (CURRENTLY AMENDED) The method according to claim 1, wherein said modifying in steps ~~(A) and~~ (B) and (C) comprises:

cropping (i) scaling each of said frames to a first size, wherein after said scaling step said first region of each frame is equal to a size of said frame prior to said scaling step and (ii) cropping each of said scaled frames, wherein said cropped frames comprise only said first region equaling ~~a~~ the size of said frames prior to said ~~modifying~~ scaling steps.

6. (PREVIOUSLY PRESENTED) The method according to claim 5, wherein said first size fills said first region.

7. (ORIGINAL) The method according to claim 1, wherein said video signal comprises a digital video signal.

8. (ORIGINAL) The method according to claim 1, wherein said first region comprises an active region.

9. (ORIGINAL) The method according to claim 1, wherein said modifying in steps (A) and (B) comprises:

obscuring a start of an active video in at least one of said frames.

10. (ORIGINAL) The method according to claim 1, wherein: step (C) comprises modifying said frames of said second segment from said second signature to said first signature.

11. (CURRENTLY AMENDED) An apparatus for processing a video signal comprising:

means for receiving said video signal comprising (i) a first segment having a series of frames, wherein (a) each of said frames of said first segment has having a first region and a second region, and (b) said first region and said second region of said first segment define defining a first signature for each of said frames of said first segment and (ii) a second segment having a series of frames, wherein (a) each of said frames of said second segment has having a first region and a second region, and (b) said first region and said second region of said second segment define

~~defining a second signature for each of said frames of said second segment;~~

means for modifying each of said frames of said first segment from said first signature to a third signature, wherein said first segment comprises a non-commercial program; and

means for modifying each of said frames of said second segment from said second signature to a fourth signature.

12. (ORIGINAL) The apparatus according to claim 10, wherein said video signal comprises a digital video signal.

13. (CURRENTLY AMENDED) An apparatus for processing a video signal comprising:

a circuit configured to receive said video signal comprising (i) a first segment having a series of frames, wherein (a) each of said frames of said first segment has ~~having~~ a first region and a second region, and (b) said first region and said second region of said first segment define ~~defining~~ a first signature for each of said frames of said second segment and (ii) a second segment having a series of frames, wherein (a) each of said frames of said second segment has ~~having~~ a first region and a second region, and (b) said first region and said second region of said second segment define ~~defining~~ a second signature for each of said frames of said second segment, wherein said circuit (i)

15 modifies each of said frames of said first segment from said first signature to a third signature and (ii) modifies each of said frames of said second segment from said second signature to a fourth signature, wherein said first segment comprises a non-commercial program.

14. (PREVIOUSLY PRESENTED) The apparatus according to claim 13, wherein said video signal comprises a digital video signal.